

# NMS Client Station

## NMS CLIENT 7-4U-II

### KEY FEATURES

### KEY FEATURES

- Monitorizare de pana la 70 canale
- Rezolutie suportata pana la 4000 x 3000
- Suporta pana la 6 monitoare simultane
- Sistem de operare: Microsoft Windows 10 IoT
- Sistem de inregistrare si monitorizare: NMS (Novus Management System)
- Compatibil cu toate NVR-urile NMS
- Integrare cu: inregistratoarele AHD NOVUS, sisteme SSWiN DSC, sisteme NMS ANPR, sisteme POS (Posnet, Upos si altele)

### DIMENSIUNI

<b>Video</b>	
IP Cameras	up to 70 channels at 640 x 480 resolution resolution using H.264 codec (video + audio) up to 55 channels at 640 x 480 resolution resolution using H.265 codec (video + audio)
Maximum Supported Camera Resolution	4000 x 3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Protocols	Novus, ONVIF, RTSP
Support dualstreaming	da
<b>Display</b>	
Monitor Output	2 x HDMI 2.0b, 2 x Display Port 1.2, 2 x Dual link-DVI, (do 6 monitorów jednocześnie)
Maximum Resolution	6 x 4K UltraHD
<b>Audio</b>	
Audio input	1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Audio Output	1 x линейный (3,5мм), 2 x HDMI, 2 x Display Port
<b>Performance - H.264</b>	
2MPX IP Camera	Display up to: 70 sub streams or 20 main streams Playback up to: 20 main streams
4MPX IP Camera	Display up to: 70 sub streams or 13 main streams Playback up to: 13 main streams
5MPX IP Camera	Display up to: 60 sub streams or 8 main streams Playback up to: 8 main streams
8MPX IP Camera	Display up to: 40 sub streams or 5 main streams Playback up to: 5 main streams
12MPX IP Camera	Display up to: 35 sub streams or 8 main streams Playback up to: 8 main streams
<b>Performance - H.265</b>	
2MPX IP Camera	Display up to: 55 sub streams or 15 main streams Playback up to: 15 main streams
4MPX IP Camera	Display up to: 50 sub streams or 8 main streams Playback up to: 8 main streams
5MPX IP Camera	Display up to: 60 sub streams or 5 main streams Playback up to: 5 main streams
8MPX IP Camera	Display up to: 65 sub streams or 4 main streams Playback up to: 4 main streams
12MPX IP Camera	Display up to: 32 sub streams or 4 main streams Playback up to: 4 main streams
<b>Playback</b>	
Cautare inregistrari	dupa data/timp, evenimente, "Text-in"
<b>Backup</b>	
Metode backup	port USB (HDD sau stick memorie), retea
<b>Stocare</b>	
Stocare interna	se poate monta: 1 x HDD 3,5" SATA
<b>Network</b>	
Interfață de rețea	1 x Ethernet - interfață RJ-45, 10/100/1000 Mbit/s
Latime de banda	350 Mb/s in total from all NVRs
Protocole de rețea suportate	HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DNS, NTP, RTSP, UPnP, SMTP
Mobile applications	NMS Mobile
<b>PTZ</b>	
Funcții PTZ	pan/tilt/zoom, comenzi presetate, trasee, tururi, auto-scan
<b>Interfete auxiliare</b>	
Port USB	6 x USB 3.0
<b>Sistem operare</b>	
Sistem operare	Microsoft Windows 10 IoT
Sistem inregistrare si monitorizare	NMS (Novus Management System)
Mod operare	triple
OSD	limba: Poloneza, Engleza, Rusa, altele
Control	mouse si tastatura (incluse in set), retea, tastatura DCZ
Diagnostic sistem	control automat: HDD-uri, retea, pierderea conexiune camera
Securitate	protectie cu parola, filtrare IP, limitare numar de conexiuni
<b>Parametri instalare</b>	
Dimensiuni (mm)	483 (W) x 177 (H) x 505 (D)
RACK 19"	4U
Greutate	25 kg
Alimentare rețea/Consum	sursa integrată PSU 230 VAC/700 W
Power consumption/heatprint	350W/280W (without HDD for recording)
Temperatura functionare	5°C – 35°C

Attention:  
From serial number: XX 2417 4170, devices have Microsoft Windows 10 IoT operating system.  
Performance specifications described in the above are valid from serial WA 2519 5776